


ITR8307/L24

Features

- Fast response time
- High sensitivity
- Cut-Off visible wavelength
- Thin
- Compact
- Pb free
- The product itself will remain within RoHS compliant version
- Compliance with EU REACH
- Compliance Halogen Free(Br < 900ppm, Cl < 900ppm, Br+Cl < 1500ppm)



Description

ITR8307/L24 is a light reflection switch which includes a GaAs IR-LED transmitter and a NPN photo-transistor with a high photosensitive receiver for short distance, operating in the infrared range. Both components are mounted side- by- side in a plastic package.


Applications

- Camera
- VCR
- Floppy disk driver
- Cassette type recorder
- Various microcomputer control equipment

Device Selection Guide

Device No.	Chip Material
IR	GaAs
PT	Silicon

Package Dimensions



- Notes:** 1.All dimensions are in millimeters
2.Tolerances unless dimensions $\pm 0.25\text{mm}$

Absolute Maximum Ratings ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Rating	Unit	
Input	Power Dissipation at(or below) 25°C Free Air Temperature	P_d	75	mW
	Reverse Voltage	V_R	6	V
	Forward Current	I_F	50	mA
	Peak Forward Current (*1) Pulse width $\leq 100\mu\text{s}$, Duty cycle=1%	I_{FP}	1	A
Output	Collector Power Dissipation	P_C	100	mW
	Collector Current	I_C	20	mA
	Collector-Emitter Voltage	$B V_{CEO}$	35	V
	Emitter-Collector Voltage	$B V_{ECO}$	6	V
Operating Temperature	T_{opr}	-25~+85	-25~+70	
Storage Temperature	T_{stg}	-30~+90	-30~+80	
Lead Soldering Temperature (*2)	T_{sol}	260	260	

Notes: (* 1) $t_w=100 \mu\text{sec.}$, $T=10 \text{ msec.}$ (* 2) $t=5 \text{ Sec}$

Electro-Optical Characteristics (Ta=25°C)

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Input	Forward Voltage	V_F	---	1.2	1.4	V	$I_F=20mA$
	Reverse Current	I_R	---	---	10	μA	$V_R=6V$
	Peak Wavelength	λ_p	---	940	---	nm	---
Output	Dark Current	I_{CEO}	---	---	1	nA	$V_{CE}=10V$ $E_e=1mW/cm^2$
Transfer Characteristics	Light Current	$I_{C(ON)}$	0.5	3.0	15.0	mA	$V_{CE}=2V,$ $I_F=4mA$
	Leakage Current	I_{LEAK}	-	-	5	μA	$V_{CE}=2V,$ $I_F=4mA$
	Rise time	t_r	-	80	400	μs	$V_{CE}=2V$ $I_C=10mA$
	Fall time	t_f	-	70	400	μs	$R_L=100\Omega,$ $d=1mm$







Rank

Conditions : $I_F=4mA$ $V_{CE}=2V$







Unit: mA

Bin number	Min	Max
B	0.50	1.10
C	0.90	1.90
D	1.45	3.20
E	2.45	5.40
F	4.05	8.90
G	6.30	15.0

Typical Electrical/Optical/Characteristics Curves for IR



Typical Electrical/Optical/Characteristics Curves for PT



Typical Electrical/Optical/Characteristics Curves for ITR

Fig.7 Relative Collector Current vs. Distance between Sensor and Al Evaporation Galss





Fig.8 Relative Collector Current vs. Card Moving Distance (l)








Fig.9 Response Time vs. Load Resistance




Packing Specification


1. Bag



2. Box



3. Carton



UNIT : cm

EVERLIGHT

CPN:

P/N:



ITR8307/L24/F43

QTY:



CAT:

HUE:

REF:

LOT NO:

MADE IN TAIWAN

Packing Quantity

1. 1000Pcs/1Bag
2. 1Bag/1Carton

Recommended Method of Storage

- The following are general recommendations for moisture sensitive level (MSL) 4 storage and use:
- Shelf life in sealed bag: 12 months at $< 40\text{ }^{\circ}\text{C}$ and $< 90\%$ relative humidity (RH)
- After bag is opened, devices that will be subjected to reflow solder or other high temperature process must
 - a) Mounted within 72 hours of factory conditions $< 30\text{ }^{\circ}\text{C}/60\%$ RH, or
 - b) Stored at $< 20\%$ RH
- Devices require bake, before mounting, if:
Humidity Indicator Card is $> 20\%$ when read at $23 \pm 5\text{ }^{\circ}\text{C}$
- If baking is required, devices may be baked:
 - a) 192 hours at $40\text{ }^{\circ}\text{C}$, and $< 5\%$ RH(dry air/nitrogen) or
 - b) 96 hours at $60\text{ }^{\circ}\text{C}$, and $< 5\%$ RH for all device containers
 - c) 24 hours at $125\text{ }^{\circ}\text{C}$

DISCLAIMER

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.
2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.
3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.
6. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.